

## Rod ends GAR8-DO (Series GAR..-DO)

with external thread, requiring maintenance, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	8 mm	Tolerance: 0/-0,008
d2	24 mm	
l2	54 mm	
	0,023 - 0,068 mm	Radial internal clearance CN
B	8 mm	Tolerance: 0/-0,12
C1	6 mm	
D	16 mm	
d1	10,2 mm	
d3	M8	
dk	13 mm	
h	42 mm	
l1	22 mm	

$l_7$	14 mm	
$r_{1s \text{ min}}$	0,3 mm	Chamfer dimension
$\alpha$	15 °	
	Without relubrication facility	
$m$	0,029 kg	Mass
$C_r$	5590 N	Basic dynamic load rating, radial
$C_{0r}$	12900 N	Basic static load rating, radial Basic load rating of housing



