



Image may differ from product. See technical specification for details.



TMHP 10E

Hydraulic jaw puller kit

The TMHP 10E is a complete puller kit for bearing dismounting. The kit includes three different arm sets that can be used in a 2-arm or 3-arm configuration. The puller uses a hydraulic spindle for easy dismounting with dismounting forces up to 100 kN (11.2 US ton). With a stroke of 80 mm (3.1 in.), the spindle facilitates dismounting in one operation. Safety is supported through a self-locking arms that reduce puller slippage under load, a spring-loaded centre point to enable easy spindle centring and a safety valve to prevent puller overload.

- Versatile kit with three different arm lengths usable in 2-arm or 3-arm configuration
- Effortless dismounting with hydraulic spindle
- Self-locking arms minimise risks of slippage under load
- Spring-loaded centre point allows easy puller centring
- Supplied with three hydraulic spindle extension pieces to allow quick adaptation to required pulling length
- Hydraulic spindle is equipped with safety valve to prevent puller overload

Overview

Dimensions

Workpiece outer diameter range, using arms	Set 1: 75 to 170 mm Set 2: 80 to 250 mm Set 3: 110 to 280 mm
Reach, using arms (max)	Set 1: 115 mm Set 2: 160 mm Set 3: 200 mm
Claw height	8 mm
Claw length	15 mm
Claw width	25 mm
Hydraulic spindle, piston stroke	80 mm
Puller adaptor thread	UN 1.5 x 16 tpi
Total spindle length	655 mm (incl. 3 available extension pieces)

Properties

Recommended applications	For dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft. Can be used as two armed puller if space around the component is restricted.
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Yes
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Yes
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Yes
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	No
Suitable for workpiece dismounting from a Housing	No
Suitable for bearing type(s)	All
Dismounting force generation	Hydraulic spindle (TMHS 100)
Special features	Centring and self locking system for firm grip of the component Useable as 2 or 3 armed puller, Provided with 3 different arm sets, Provided with various spindle extension pieces to quickly adapt the reach Hydraulic spindle with integrated safety valve for safer use
Pulling force (max)	100 kN
Total number of arms in kit	3 sets of 3
Arms	Set 1 (TMHP 10E-10) with arm length 190 mm Set 2 (TMHP 10E-11) with arm length 240 mm Set 3 (TMHP 10E-12) with arm length 285 mm
Spindle nose piece	yes, \varnothing 30mm
Colour	Black Silver
Material	Alloy engineering steels, hardened and tempered

Coating	Black phosphated, Hydraulic spindle with trivalent chromium parts
Recommended storage temperature	5.0 – 40.0 °C
Relative humidity	max 75%
Case dimensions (l x h x w)	580 x 410 x 70 mm
Content	<ul style="list-style-type: none"> 1 x arm-assembly stand 3 x arms, set 1 (TMHP 10E-10) 3 x arms, set 2 (TMHP 10E-11) 3 x arms, set 3 (TMHP 10E-12) 1 x hydraulic spindle TMHS 100 (with handle bar) 3 x extension pieces for hydraulic spindle: 50, 100, 150 mm 1 x nosepiece with centre point for hydraulic spindle IFU QR Code card Case

Logistics

Product net weight	15 kg
eClass code	23-05-19-01
UNSPSC code	27111712

Compatible products

Spare part

Spare arm, 190 mm (7.5 in) long, for Hydraulic jaw puller kit and Hydraulic puller kit	3 x TMHP 10E-10
Spare arm, 240 mm (9.4 in) long, for Hydraulic jaw puller kit	3 x TMHP 10E-11
Spare arm, 285 mm (11.2 in) long, for Hydraulic jaw puller kit	3 x TMHP 10E-12
Spare four arm stand with bolts and nuts for Hydraulic jaw puller kit and Hydraulic puller kit	TMHP 10E-5
Advanced hydraulic spindle, 100 kN	TMHS 100
Advanced hydraulic spindle, 100 kN, spindle only	TMHS 100-1
Spare set of extension pieces and nose piece for Hydraulic spindles	TMHS 8T

Accessory

Spare arm, 140 mm (5.5 in) long for Hydraulic puller kit	3 x TMHP 10E-9
--	--------------------------------

Tri-section pulling plate	TMS 100
Puller protection blanket	TMMX 210
Puller protection blanket	TMMX 280
Puller protection blanket	TMMX 350



Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using [YouTube API Services](#)), you agree to be bound by the [YouTube Terms of Service](#).

Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

Changes

SKF reserves the right to make changes or additions to this website / app at any time.